

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1044>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

1.438 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.390 inches and 0.410 inches

Overall Height:

0.622 inches

Overall Width:

0.609 inches

Mounting Slot Width:

Between 0.138 inches and 0.146 inches

Body Mounting Hole Accommodation Length:

1.000 inches

Body Mounting Hole Accommodation Width:

0.625 inches

Distance Between Mounting Facility Centers:

Between 1.344 inches and 1.406 inches

Mounting Hole Style:

Rectangular, w/external slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

3.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

14

Projection Length Below Mounting Surface:

0.481 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Symmetrical

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Furnished Items And Quantity:

4 lock washer and 4 screw and 4 stud

Terminal Type And Quantity:

14 solder well

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300