

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1052>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Right angle type

Overall Length:

2.100 inches

Overall Width:

0.702 inches

Body Height:

0.375 inches

Environmental Protection:

Cold resistant and heat resistant

Distance Between Mounting Facility Centers:

1.850 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.195 inches

Thread Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-20693, type 1 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right hand and jackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.