

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1061>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Overall Height:**

0.680 inches

**Overall Diameter:**

0.312 inches

**Environmental Protection:**

Humidity resistant and shock proof and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Frequency Rating:**

18000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Shrinkable tubing

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thread Length:**

0.123 inches

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.