

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1066>

Body Style:

Straight shape

Overall Length:

2.550 inches

Overall Height:

0.625 inches

Overall Width:

0.250 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.