

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1073>

Overall Length:

0.906 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.800 inches

Overall Height:

1.313 inches

Overall Width:

0.500 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock proof and vibration resistant

Unthreaded Mounting Hole Diameter:

0.218 inches

Cable Entrance Diameter:

0.212 inches

Distance From Mounting Shoulder To Rear Face:

0.641 inches

Flange Length:

1.250 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Qq-s-365, type 2, grade a 1st treatment response clear printed value single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365, type 2, grade a federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp.22, 1/2 h federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Color:

Natural

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0