

View Online at <https://aerobasegroup.com/nsn/5935-01-021-1087>

**Body Style:**

Straight shape w/cable clamp

**Bushing Diameter:**

0.500 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.136 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.531 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.531 inches

**Cable Entrance Diameter:**

0.087 inches

**Distance From Mounting Shoulder To Front Face:**

0.594 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact and body surfaces silver

**Precious Material And Weight:**

0.001 gold grains, troy and 0.101 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0