

View Online at <https://aerobasegroup.com/nsn/5935-01-021-3100>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, w/o cable clamp

Overall Diameter:

1.890 inches

Body Angle In Deg:

90.0

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20-11 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Distance From Centerline To Connector End:

2.305 inches

Distance From Centerline To Cable End:

1.969 inches

Thread Length:

0.290 inches and 0.375 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.188 inches and 1.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1, grade b federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Included Contact Quantity:

13 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.013 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms3108 government standard

Shelf Life:

N/a

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.