Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-021-3795

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.305 inches

Overall Height:

0.730 inches

Overall Width:

0.370 inches

Distance Between Mounting Facility Centers:

4.045 inches

Board Accommodated Length:

3.625 inches single board

Threaded Device Type:

Mounting hole

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end



Terminal Type: Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping **Included Contact Quantity:** 56 single mating end single contact grouping **Included Contact Type:** Bifurcated spring single mating end single contact grouping **Special Features:** Polarizing key part number is 122795-01 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.056 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0