NSN 5935-01-021-9230

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-021-9230 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 1.375 inches **Bushing Diameter:** 0.468 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.718 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.718 inches **Cable Entrance Diameter:** 0.217 inches **Distance From Mounting Shoulder To Front Face:** 0.625 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** N single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:**

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping

NSN 5935-01-021-9230

A039b0

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiio