Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-022-6542

Body Style:
Straight shape
Overall Length:
2.685 inches
Overall Height:
0.740 inches
Overall Width:
0.610 inches
Unthreaded Mounting Hole Diameter:
0.099 inches
Distance Between Mounting Facility Centers:
2.352 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Lever-pivot assembly spring action
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Zinc and chromate
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.036 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0