## NSN 5935-01-022-9076

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-022-9076 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.594 inches **Overall Diameter:** 0.375 inches **Distance From Mounting Shoulder To Front Face:** 0.426 inches **Mounting Facility Thickness:** 0.094 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 4000.0 megahertz single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 75.0 single mating end single contact grouping Thready Qty Per Inch (tpi):

32 and 32

**Thread Size:** 

0.313 inches and 0.313 inches

## NSN 5935-01-022-9076

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location:  |
|---|
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and copper single mating end single contact grouping               |
| Insert Material:  |
| Plastic tetrafluoroethylene single mating end   |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Contact Material Specification:   |
| Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping |
| Shell Material:   |
| Copper alloy  |
| Shell Surface Treatment:  |
| Nickel  |
| Shell Material Specification:   |
| Qq-b-626, comp 1/2 h federal specification single material response   |
| Included Contact Quantity:  |
| 1 single mating end single contact grouping   |
| Bushing Accommodation Hole Shape:   |
| Round keyed   |
| Included Contact Type:  |
| Coaxial pin single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.005 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Unef and unef   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |