NSN 5935-01-023-2494

Electrical Plug Connector - Page 1 of 2

Solder well single mating end single contact grouping



View Online at https://aerobasegroup.com/nsn/5935-01-023-2494

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.219 inches
Overall Diameter:
0.562 inches
Cable Entrance Diameter:
0.175 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Frequency Rating:
4000.0 megahertz single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:

NSN 5935-01-023-2494Electrical Plug Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0