## NSN 5935-01-023-2509

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-023-2509

Body Style:
Straight shape
Overall Length:
2.729 inches
Overall Width:
0.494 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:

**Included Contact Type:** 

Round socket single mating end single contact grouping

37 single mating end single contact grouping

## NSN 5935-01-023-2509

Electrical Receptacle Connector - Page 2 of 2



Precious M	lateriai <i>P</i>	∖nd Lo	cation
------------	-------------------	--------	--------

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.037 gold grains, troy and 0.037 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.