

View Online at <https://aerobasegroup.com/nsn/5935-01-023-3019>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Pcb, angle shape, external coupling

**Overall Length:**

0.580 inches

**Overall Height:**

0.525 inches

**Overall Width:**

0.250 inches

**Environmental Protection:**

Corrosion resistant and fungus proof and humidity resistant and moisture resistant and shock proof and vibration resistant and salt water resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

7000.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

7000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Beryllium single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, calss 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 1/2 h federal specification single material response single mating end single contact grouping

**Shell Material:**

Steel comp 303

**Shell Material Specification:**

Qq-s-763, class 303, cond a federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.