NSN 5935-01-023-3528

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-023-3528 **Thread Class:** 2a **Thread Pitch Diameters:** +0.225/+0.229 inches **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Orange **Body Style:** Threaded bushing mounted **Overall Length:** Between 0.922 inches and 1.000 inches **Mounting Bushing Length:** Between 0.375 inches and 0.438 inches **Body Length:** Between 0.500 inches and 0.672 inches **Overall Diameter:** 0.281 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Test prod stepped single finger **Finger Accommodation Diameter:** 0.050 inches single finger and 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches

Turret

Terminal Type:

NSN 5935-01-023-3528

Tip Jack - Page 2 of 2



Material:
Copper alloy terminal
Material:
Plastic polyamide insulator
Surface Treatment:
Gold spring
Surface Treatment:
Gold spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A03400