Tip Jack - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-023-3531



**Thread Class:** 

2a

**Thread Pitch Diameters:** 

+0.225/+0.229 inches

Thread Direction:

**Right-hand** 

**Electrical Insulation Feature:** 

Insulated completely

Identification Code Color:

Gray

Body Style:

Threaded bushing mounted

#### **Overall Length:**

Between 0.922 inches and 1.000 inches

#### Mounting Bushing Length:

Between 0.375 inches and 0.438 inches

#### **Body Length:**

Between 0.500 inches and 0.672 inches

#### **Overall Diameter:**

0.281 inches

### **Bushing Accommodation Hole Shape:**

Round

# Maximum Voltage Rating In Volts:

2000.0 ac

#### Accommodated Finger Type:

Test prod stepped single finger

#### Finger Accommodation Diameter:

0.050 inches single finger and 0.080 inches single finger

#### Finger Accommodation Length:

0.500 inches single finger

#### Bushing Thru-hole Accommodation Diameter:

0.250 inches

#### **Current Rating In Amps:**

5.0

#### Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

## Thread Size:

0.250 inches

### **Terminal Type:**

Turret

# NSN 5935-01-023-3531

Tip Jack - Page 2 of 2

Material:

Copper alloy terminal

Material:

Plastic polyamide insulator

Surface Treatment:

Gold spring

Surface Treatment:

Gold spring

# Thread Series Designator:

Unef

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A03400

