

View Online at <https://aerobasegroup.com/nsn/5935-01-023-4836>

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.750 inches and 1.000 inches

Overall Diameter:

0.320 inches

Environmental Protection:

Shock proof and vibration resistant

Cable Entrance Diameter:

0.116 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.