

View Online at <https://aerobasegroup.com/nsn/5935-01-023-4853>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.275 inches and 1.340 inches

Overall Diameter:

Between 1.380 inches and 1.400 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

Between 0.555 inches and 0.575 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

18-85 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

116.0 and 160.0 and 191.0 and 311.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

28

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-367, comp 6061, t6 federal specification single material response

Included Contact Quantity:

85 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.085 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Specification Data:

81349-mil-c-81511/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.