NSN 5935-01-023-4857

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-023-4857

Body	Stv	le٠
Bouv	JLV	ıc.

Angle shape flange mount, external coupling

Overall Width:

1.280 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.968 inches

Cable Entrance Diameter:

0.620 inches

Distance From Mounting Shoulder To Front Face:

0.530 inches

Flange Length:

1.280 inches

Mating End Quantity:

Contact Position Arrangement Style:

27-8 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Cable End:

0.860 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

NSN 5935-01-023-4857

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

6 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0