Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-023-8259

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.420 inches
Overall Diameter:
1.777 inches
Environmental Protection:
Pressure proof and humidity resistant and shock proof and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
24-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
270.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.290 inches
Thread Size:
1.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating and single contact grouping

Crimp single mating end single contact grouping

# NSN 5935-01-023-8259

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

#### **Shell Material Specification:**

Qq-a-367 federal specification single material response

# Included Contact Quantity:

61 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.061 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

Specification Data:

81349-mil-c-83723/42 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.