NSN 5935-01-023-8268

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-023-8268 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** Between 1.115 inches and 1.185 inches **Overall Height:** Between 0.792 inches and 0.832 inches **Overall Width:** Between 0.792 inches and 0.832 inches **Environmental Protection:** Moisture resistant and weather resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.589 inches and 0.599 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.589 inches and 0.599 inches **Distance From Mounting Shoulder To Front Face:** Between 0.406 inches and 0.416 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 40393 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-01-023-8268

Electrical Receptacle Connector - Page 2 of 2



Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
10
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0