NSN 5935-01-023-9171

Right-hand and right-hand and right-hand

Thread Class: 2a and 2b and 2a Thread Direction:

Body Style: Straight shape Overall Length: 0.850 inches Overall Height:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-023-9171

| 0.694 inches | |
|---|--|
| Overall Width: | |
| 0.250 inches | |
| Distance Between Mounting Facility Centers: | |
| 0.650 inches | |
| Threaded Device Type: | |
| Coupling facility and mounting stud | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 2 rows of contacts non-inserted board single mating end | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Contact Maximum Current Rating In Amps: | |
| 5.0 single mating end single contact grouping | |
| Contact Maximum Ac Voltage Rating In Volts: | |
| 1000.0 single mating end single contact grouping | |
| Polarization Method: | |
| Jackscrew | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Thready Qty Per Inch (tpi): | |
| 56 and 56 and 56 | |
| Thread Size: | |
| 0.086 inches and 0.086 inches and 0.086 inches | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping and copper single mating end single contact grouping | |
| Insert Material: | |
| Plastic polyphenylene single mating end | |
| | |
| | |

NSN 5935-01-023-9171

Electrical Receptacle Connector - Page 2 of 2



| Terminal [*] | Type: |
|-----------------------|-------|
|-----------------------|-------|

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-female and location-left hand topandjackscrew type-male and location-right hand bottom

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-24519 spec.