Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-024-1881

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.128 inches

Overall Height:

1.125 inches

Overall Width:

1.125 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

14-15 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20

Thread Size:

0.937 inches

Electrical Receptacle Connector - Page 2 of 2



	Location: gle mating end single contact grouping
	Surface Treatment:
-	le mating end single contact grouping
	Surface Treatment Specification:
-	04 military specification single treatment response single mating end single contact grouping
Terminal	
	ell single mating end single contact grouping
Shell Mat	
Steel	rface Treatment:
Nickel	nace freatment:
	rface Treatment Specification.
	rface Treatment Specification:
	74, class 1 military specification single treatment response
	Contact Quantity: mating end single contact grouping
-	Contact Type:
	n single mating end single contact grouping
-	Material And Location:
	surfaces gold
	Material And Weight:
	d grains, troy
-	Material:
Gold	
	eries Designator:
Unef	
Shelf Life	
N/a	
Unit Of N	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	
	nilitary Standard):
-	04 spec.