

View Online at <https://aerobasegroup.com/nsn/5935-01-024-5502>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

1.172 inches

**Overall Diameter:**

1.391 inches

**Cable Entrance Diameter:**

Between 0.600 inches and 0.635 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-53 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

550.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

53 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.053 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0