## NSN 5935-01-024-9162

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-024-9162 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 342.0 and 211.0 and 168.0 and 101.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp Thread Length: 0.322 inches Thread Size:

**Terminal Location:** 

1.438 inches

Back single mating end single contact grouping

## NSN 5935-01-024-9162

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



| Contact Material:   |
|---|
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Contact Surface Treatment Specification:  |
| Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy 6061   |
| Shell Surface Treatment:  |
| Anodize   |
| Shell Surface Treatment Specification:  |
| Mil-a-8625 military specification single treatment response   |
| Shell Material Specification:   |
| Qq-a-367, t6 federal specification single material response   |
| Included Contact Quantity:  |
| 55 single mating end single contact grouping  |
| Included Contact Type:  |
| Round pin single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.055 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Unef  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |