NSN 5935-01-025-2145

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-2145 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 2.125 inches **Overall Diameter:** 1.969 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28-18 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 4th contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 145.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring **Thread Length:** 0.467 inches and 0.664 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.750 inches and 1.750 inches **Terminal Location:**

Back single mating end single contact grouping

NSN 5935-01-025-2145Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic silicone mineral filled single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Type:
Round pin single mating end all contact groupings
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns and uns
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0