NSN 5935-01-025-2150

Electrical Plug Connector - Page 1 of 2

Tab, solder lug single mating end single contact grouping



View Online at https://aerobasegroup.com/nsn/5935-01-025-2150

Thread Class:
2b
Thread Direction:
Right-hand
·
Body Style:
Straight shape, internal coupling
Overall Length:
2.312 inches
Overall Diameter:
0.812 inches
Environmental Protection:
Shock proof and vibration resistant
Cable Entrance Diameter:
0.375 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:

NSN 5935-01-025-2150Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface(gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0