NSN 5935-01-025-2209

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-2209

Body Style: Right angle type **Overall Length:** 4.330 inches **Overall Width:** 0.460 inches **Body Height:** 0.340 inches **Environmental Protection:** Shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 4.030 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Contact **Terminal Location:** Side single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 20 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

NSN 5935-01-025-2209

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Polarized position at 04 and 07
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

A039b0

Mil-m-14 spec.