Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-2327

2b Thread Direction: Right-hand Seal Material: Any acceptable Overall Length: 1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Quy Per Inch (tpi): 20 Pinead Size: 0.338 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Straight type w/strain relief Straight type Straight type April Unef Straight type Straight type Straight type Straight		
Thread Direction: Right-hand Seal Material: Any acceptable Overall Length: 1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Overall Diameter: Any acceptable Overall Diameter: Any acceptable Overall Diameter: Oxfore Diameter:	Thread Class:	
Right-hand Seal Material: Any acceptable Overall Length: 1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Straight type wistrain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shef Lifte: Na Unef Shef Lifte: Na Unit Of Measure: To		
Seal Material: Any acceptable Overall Length: 1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: N/a Unit of Measure: Na		
Any acceptable Overall Length: 1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Threadd coupling Threadd Size: 0.338 inches Material: Aluminum alloy Surface Treatment: Cadmium Stright type w/strain relief Surface Treatment: Cadmium Stright type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Undef Shelf Life: N/a Unit of Measure: N/a	-	
Overall Length:1.125 inchesBody Length:Any acceptableOverall Diameter:Any acceptableCable Opening Diameter:0.750 inchesCable Opening Quantity:1Seal Type:BushingSize Designation:16Mounting Facility Type And Quantity:1 threaded couplingThread Size:0.938 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStriaght type w/strain reliefSurface Treatment:CadmiumThread Sories Designator:Uriagit type w/strain reliefSurface Treatment:CadmiumThread Sories Designator:Uring type w/strain reliefSurface Treatment:CadmiumThread Sories Designator:UnefShelf Life:NaUnefShelf Life:NaUnit of Measure:To tool Source:Tool Sourc	Seal Material:	
1.125 inches Body Length: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Stringist type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Dird Measure: Via	Any acceptable	
Body Length: Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Style Designator: Straght type wistrain relief Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: N/a Unef Sheff Life: N/a Unef Cadmium	Overall Length:	
Any acceptable Overall Diameter: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Scable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type wistrain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	1.125 inches	
Overall Diameter:Any acceptableCable Opening Diameter:0.750 inchesCable Opening Quantity:1Seal Type:BushingSize Designation:16Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):20Thread Size:0.938 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Citraight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefSheff Life:NaUnefSheff Life:NaUnefSheff Life:NaUnt Of Measure:	Body Length:	
Any acceptable Cable Opening Diameter: O.750 inches Cable Opening Quantity: Cable Opening Cable Openin	Any acceptable	
Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Stright type w/strain relief Surface Treatment: Cadmium Stright type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: Na Unef Sheff Life: Na Unef Sheff Life: Na Unef Sheff Life: Na Unit of Measure: Tot of Measure: Surface Treatment: Surface Treatment: Musterial Surface Treatment: Surface Treatment: Cadmium <	Overall Diameter:	
0.750 inches Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: Na Unof Measure: Na	Any acceptable	
Cable Opening Quantity: 1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Strige Treatment: Cadmium Thread Series Designator: Unif Thread Series Designator: Unif Shelf Life: N/a Unif Shelf Life: N/a Unit Of Measure: -	Cable Opening Diameter:	
1 Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: -	0.750 inches	
Seal Type: Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Cadmium Thread Series Designator: Unef Sheft Life: Na Unef Sheft Life: Na Unit Of Measure: -	Cable Opening Quantity:	
Bushing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	1	
Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Seal Type:	
16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Bushing	
Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Hunei Surface Treatment: Cadmium Straight type w/strain relief Surface Treatment: Cadmium Hunei Cadmium Unef Shelf Life: N/a Unit Of Measure: -	Size Designation:	
1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	16	
Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Mounting Facility Type And Quantity:	
20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	1 threaded coupling	
Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Thready Qty Per Inch (tpi):	
0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Untof Measure:	20	
Material:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:	Thread Size:	
Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	0.938 inches	
Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Material:	
Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Aluminum alloy	
Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Surface Treatment:	
Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Cadmium	
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Style Designator:	
Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:	Straight type w/strain relief	
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: 	Surface Treatment:	
Unef Shelf Life: N/a Unit Of Measure:	Cadmium	
Shelf Life: N/a Unit Of Measure: 	Thread Series Designator:	
N/a Unit Of Measure: 	Unef	
Unit Of Measure:	Shelf Life:	
	N/a	
	Unit Of Measure:	
Demilitarization:	Demilitarization:	
No	No	

NSN 5935-01-025-2327

Electrical Connector Backshell - Page 2 of 2

Fiig: A10100

