Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-2752

#### **Overall Length:**

Between 0.508 inches and 0.571 inches

#### **Overall Height:**

1.141 inches

## **Overall Width:**

1.141 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

#### **Distance From Mounting Shoulder To Front Face:**

Between 0.462 inches and 0.493 inches

#### Mating End Quantity:

1

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

## Connector Locking Method:

Bayonet pin

## **Insert Material:**

Plastic silicone single mating end

# Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Nickel

# Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-83723/45 government specification

#### Shelf Life:

N/a

- Unit Of Measure:
- ---
- Demilitarization:
- No

# NSN 5935-01-025-2752

Receptacle Dummy Connector - Page 2 of 2

**Fiig:** A039b0

