## NSN 5935-01-025-4424

Thread Class: 2a and 2b

**Thread Direction:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-4424

Right-hand and right-hand
Body Style:
Straight shape w/screw locks
Overall Length:
1.250 inches
Overall Height:
0.656 inches
Overall Width:
0.390 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.099 inches and 0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Mil-m-14, type sdg-f military specification single material response single mating end

## NSN 5935-01-025-4424

Electrical Plug Connector - Page 2 of 2



## **Included Contact Quantity:** 34 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

Mil-m-14 spec.

Mil-std (military Standard):

A039b0