

View Online at <https://aerobasegroup.com/nsn/5935-01-025-4694>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.225/+0.229 inches

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Red

**Body Style:**

Threaded bushing mounted

**Overall Length:**

Between 0.922 inches and 1.000 inches

**Mounting Bushing Length:**

Between 0.375 inches and 0.438 inches

**Body Length:**

Between 0.500 inches and 0.672 inches

**Overall Diameter:**

0.281 inches

**Bushing Accommodation Hole Shape:**

Round

**Maximum Voltage Rating In Volts:**

2000.0 ac

**Accommodated Finger Type:**

Test prod stepped single finger

**Finger Accommodation Diameter:**

0.050 inches single finger and 0.080 inches single finger

**Finger Accommodation Length:**

0.500 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

0.250 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Turret

**Material:**

Copper alloy terminal

**Material:**

Plastic polyamide insulator

**Surface Treatment:**

Gold spring

**Surface Treatment:**

Gold spring

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400