Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-025-7039

View Online at https://aerobasegroup.com/nsn/5935-01-025-7039
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.125 inches
Overall Diameter:
2.719 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40-56 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
144.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
16 and 16
Thread Size:
2.500 inches and 2.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic silicone mineral filled single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:

Aluminum

# NSN 5935-01-025-7039

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

#### Cadmium

## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Included Contact Quantity:**

85 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.085 gold grains, troy

Precious Material:

Gold

#### Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Un and un

Specification Data:

81349-mil-c-5015 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0