NSN 5935-01-025-7090

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-7090 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.141 inches **Overall Diameter:** 0.484 inches **Environmental Protection:** Weatherproof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Silver

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-025-7090

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Ground attached
Precious Material And Location:
Body surface silver
Precious Material And Weight:
0.100 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0