NSN 5935-01-025-7128

Thread Class: 2a and 2b

Body Style:

Thread Direction:

Rectangular shape

Right-hand and right-hand

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-7128

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 3.500 inches |
|---|
| Overall Height: |
| 1.390 inches |
| Overall Width: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.150 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-104 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Size: |
| 0.138 inches and 0.138 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic phenol-formaldehyde single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| |

NSN 5935-01-025-7128

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 104 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.104 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |