Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-025-9108

# Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

## **Overall Length:**

2.125 inches

## **Overall Diameter:**

2.719 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

#### Threaded Device Type:

Back shell and coupling facility

#### Mating End Quantity:

1

# Contact Position Arrangement Style:

40-56 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## Insert Position In Deg:

288.0

Shell Type:

Solid

#### Connector Locking Method:

Internally threaded coupling ring

#### **Thread Length:**

0.467 inches and 0.664 inches

## Thready Qty Per Inch (tpi):

16 and 16

Thread Size:

2.500 inches and 2.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

NSN 5935-01-025-9108

Electrical Plug Connector - Page 2 of 2



**Terminal Type:** 

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

85 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

#### **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un and un

**Specification Data:** 

81349-mil-c-5015 government specification

Shelf Life:

N/a

---

Unit Of Measure:

\_ ... . .

Demilitarization:

No

Fiig:

A039b0