

View Online at <https://aerobasegroup.com/nsn/5935-01-025-9136>

Thread Class:

2b and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

1.459 inches

Overall Height:

1.459 inches

Overall Width:

0.750 inches

Environmental Protection:

Moisture resistant and shock proof and salt water resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

12400.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Thread Size:

0.625 inches and 0.625 inches

Contact Material:

Copper alloy all mating ends single contact grouping or beryllium all mating ends single contact grouping and copper all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-b-626 comp 22 1/2 hard federal specification single material response all mating ends single contact grouping or qq-c-530 condh federal specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Included Contact Quantity:

2 all mating ends single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.