NSN 5935-01-025-9136

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-9136
Thread Class:
2b and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape, external/internal coupling
Overall Length:
1.459 inches
Overall Height:
1.459 inches
Overall Width:
0.750 inches
Environmental Protection:
Moisture resistant and shock proof and salt water resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
N all mating ends
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Frequency Rating:
12400.0 megahertz all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thread Size:
0.625 inches and 0.625 inches
Contact Material:
Copper alloy all mating ends single contact grouping or beryllium all mating ends single contact grouping and copper all mating ends single
contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic tetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends single contact grouping
Contact Material Specification:

Qq-b-626 comp 22 1/2 hard federal specification single material response all mating ends single contact grouping or qq-c-530 condh federal

specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

NSN 5935-01-025-9136

Connector Adapter - Page 2 of 2



Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Included Contact Quantity:
2 all mating ends single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.