NSN 5935-01-025-9143

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-025-9143 **Thread Class:** 2b **Thread Direction:** Right-hand **Overall Length:** 0.707 inches **Overall Height:** 0.625 inches **Overall Width:** 0.260 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock proof and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.112 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.481 inches **Distance From Mounting Shoulder To Front Face:** 0.442 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 18000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 36 **Thread Size: Terminal Location:**

0.250 inches

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-025-9143

Electrical Receptacle Connector - Page 2 of 2



Insert	Mata	rial:
msert	wate	Hai.

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Material Specification:

Qq-s-763 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.