## NSN 5935-01-026-0407

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-0407 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Flange mount **Overall Length:** 0.783 inches **Overall Diameter:** 0.875 inches **Environmental Protection:** Vibration resistant and humidity resistant and shock proof **Distance From Mounting Shoulder To Rear Face:** 0.585 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Copper alloy 360

Nickel

**Shell Surface Treatment:** 

## NSN 5935-01-026-0407

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:** Qq-n-290 federal specification single treatment response **Shell Material Specification:** Qq-b-626, comp 360 federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.