## NSN 5935-01-026-0845

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-0845

**Body Style:** 

Straight shape threaded

**Overall Length:** 

1.041 inches

**Overall Diameter:** 

Between 1.084 inches and 1.104 inches

**Environmental Protection:** 

Moisture proof and salt water resistant

**Distance From Mounting Shoulder To Front Face:** 

Between 0.578 inches and 0.598 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

16-26 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Tin and nickel

**Shell Material Specification:** 

Qq-s-637 federal specification single material response

**Included Contact Quantity:** 

26 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-01-026-0845

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mounted
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0