Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-0948

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, flange mount |
| Overall Length: |
| 0.719 inches |
| Bushing Diameter: |
| 0.248 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.094 inches |
| Distance Between Mounting Facility Centers: |
| 0.531 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 36 |
| Thread Size: |
| 0.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| |

NSN 5935-01-026-0948

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Gold

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0