## NSN 5935-01-026-1618

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-1618

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 0.740 inches and 0.802 inches

**Overall Height:** 

1.141 inches

**Overall Width:** 

1.141 inches

**Environmental Protection:** 

Moisture proof and vibration proof

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.431 inches and 0.462 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-44 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

225.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Silicon single mating end and plastic single mating end

# NSN 5935-01-026-1618

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy 6061

**Shell Surface Treatment:** 

Cadmium

### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:** 

Qq-a-367, t6 federal specification single material response

**Included Contact Quantity:** 

44 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.