NSN 5935-01-026-2221

Electrical Plug Connector - Page 1 of 2



Licenseal rag connector rage rer L
View Online at https://aerobasegroup.com/nsn/5935-01-026-2221
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.531 inches
Overall Diameter:
1.968 inches
Environmental Protection:
Heat resistant and weather resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-12 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
90.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.625 inches and 1.750 inches
Terminal Location:
Back single mating end single contact grouping

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber single mating end

NSN 5935-01-026-2221Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0