NSN 5935-01-026-2225

Connector Adapter - Page 1 of 2

Insert Material Specification:

L-p-403, type 1 federal specification single material response all mating ends



View Online at https://aerobasegroup.com/nsn/5935-01-026-2225

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Angle shape, external/internal coupling
Overall Length:
2.500 inches
Overall Height:
1.500 inches
Overall Width:
0.828 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Sc all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 all mating ends all contact groupings
Contact Maximum Frequency Rating:
11000.0 megahertz all mating ends all contact groupings
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell and internally threaded coupling ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends all contact groupings
Thready Qty Per Inch (tpi):
24
Thread Size:
0.6875 inches
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic tetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings

NSN 5935-01-026-2225

Connector Adapter - Page 2 of 2



Included Contact Quantity

1 2nd mating end all contact groupings

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.