

View Online at <https://aerobasegroup.com/nsn/5935-01-026-2225>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

2.500 inches

Overall Height:

1.500 inches

Overall Width:

0.828 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sc all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

11000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

24

Thread Size:

0.6875 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings

Insert Material Specification:

L-p-403, type 1 federal specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.