# NSN 5935-01-026-2228

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-2228
Body Style:
Right angle type
Overall Length:
4.469 inches
Overall Width:
0.469 inches
Body Height:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.031 inches
Distance Between Mounting Facility Centers:
4.063 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
29 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
725.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, type mdg military specification single material response single mating end

#### **Included Contact Quantity:**

29 single mating end single contact grouping

# NSN 5935-01-026-2228

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:

Gold

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.