Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-2235

- Body Style:
- Straight type
- **Overall Length:**
- 4.855 inches

## **Overall Height:**

0.697 inches

## **Overall Width:**

Between 0.242 inches and 0.248 inches

#### **Environmental Protection:**

Moisture proof and vibration resistant and salt water resistant

#### **Unthreaded Mounting Hole Diameter:**

#### Between 0.096 inches and 0.101 inches

#### Distance Between Mounting Facility Centers:

4.565 inches

Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### Included Contact Quantity:

80 single mating end single contact grouping

# Included Contact Type:

Flat socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.080 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



## **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-c-55302/27 government specification

Shelf Life: N/a Unit Of Measure: --

**Demilitarization:** No

Fiig:

A039b0