Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-8531

## Thread Class:

2a and 2b

## **Thread Direction:**

Right-hand and right-hand

## Body Style:

Hood, top opening w/clamp

## **Overall Length:**

0.870 inches

## **Overall Height:**

1.870 inches

**Overall Width:** 

0.330 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

## Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

14 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## Polarization Method:

Jackscrew

## Shell Type:

Hood, top opening

## **Connector Locking Method:**

Jackscrew-socket

## **Connector Cable Strain Relief Method:**

Cable clamp

## Thread Size:

0.086 inches and 0.086 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping



Solder well sin	gle mating end single contact grouping
Shell Material	:
luminum alloy	/
Shell Surface	Treatment:
nodize	
Shell Surface	Treatment Specification:
/lil-a-8625 mili	tary specification single treatment response
nsert Materia	I Specification:
/lil-m-14, type	sdg-f military specification single material response single mating end
ncluded Cont	act Quantity:
4 single matir	ng end single contact grouping
ncluded Cont	tact Type:
ound socket	single mating end single contact grouping
Precious Mate	erial And Location:
Contact surfac	es gold
Precious Mate	erial And Weight:
0.014 gold grai	ins, troy
Precious Mate	erial:
Gold	
hread Series	Designator:
Jnc and unc	
Shelf Life:	
l/a	
Jnit Of Measu	ire:
-	
Demilitarizatio	on:
10	
iig:	
A039b0	
/lil-std (milita	ry Standard):
/lil-g-45204 sp	ec.