## NSN 5935-01-026-9169

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-026-9169

| Thread Oleans   |
|---|
| Thread Class:   |
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, internal coupling   |
| Overall Length:   |
| 1.250 inches  |
| Overall Diameter:   |
| 0.650 inches  |
| Environmental Protection:   |
| Shock proof and vibration resistant   |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| Tnc single mating end   |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Contact Maximum Ac Voltage Rating In Volts:   |
| 500.0 single mating end single contact grouping   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Internally threaded coupling ring   |
| Connector Cable Strain Relief Method:   |
| Compression nut   |
| Radio Frequency Type Contact Characteristic Impedance In Ohms:  |
| 50.0 single mating end single contact grouping  |
| Thread Length:  |
| 0.156 inches  |
| Thread Size:  |
| 0.438 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Contact Surface Treatment Specification:  |
| Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |

## NSN 5935-01-026-9169

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



| Included Contact Quantity:   |
|--|
| 1 single mating end single contact grouping  |
| Included Contact Type:   |
| Coaxial pin single mating end single contact grouping  |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.005 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unef   |
| Specification Data:  |
| 81349-mil-c-39012/26 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |